



Держатель предохранителя 10x38, 1 полюс

Тип **C10-SLS/32/1-L**
 № для зак. **112225**

Abbildung ähnlich

Технические характеристики согласно ETIM 6.0

| Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) | | |
|---|----|------------------|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss8.1-27-37-14-01 [AKF058010]) | | |
| Version as main switch | | No |
| Version as safety switch | | No |
| Max. rated operation voltage Ue AC | V | 690 |
| Rated permanent current Iu | A | 32 |
| Rated operation power at AC-23, 400 V | kW | 0 |
| Conditioned rated short-circuit current Iq | kA | 100 |
| Rated short-time withstand current Icw | kA | 0.3 |
| Suitable for fuses | | Shape C1-C3 |
| Number of poles | | 1 |
| With error protection | | No |
| Type of electrical connection of main circuit | | Screw connection |
| Suitable for ground mounting | | Yes |
| Suitable for front mounting 4-hole | | No |
| Suitable for busbar mounting | | No |
| Type of control element | | - |
| Position control element | | Front side |
| Motor drive optional | | No |
| Motor drive integrated | | No |
| Version as emergency stop installation | | No |
| Degree of protection (IP), front side | | IP20 |