



Аналоговый таймер, синхронный, шаг 15 мин, 1 перекл. контакт, дневная программа

Тип TSSD1NO
№ для зак. 167389
Каталог № TSSD1NO

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Номинальный ток для указания потери мощности	I_n	A	0
Потеря мощности на полюс, в зависимости от тока	P_{vid}	W	0
Потеря мощности оборудования, в зависимости от тока	P_{vid}	W	0
Статическая потеря мощности, не зависит от тока	P_{vs}	W	0.9
Способность отдавать потери мощности	P_{ve}	W	0
Мин. рабочая температура		°C	-20
Макс. рабочая температура		°C	55
			0

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Analogous time switch for distribution board (EC002304)			
Electric engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Analogous time switch (ecl@ss8.1-27-20-01-09 [ACN651008])			
Mounting method			DIN rail
Number of channels			1
Supply voltage		V	230 - 230
Voltage type of supply voltage			AC
Frequency supply voltage		Hz	50 - 50
Autonomy in hours			0
Autonomy in years			0
Autonomy per day		s	0
60 min. program			No
24 h program			Yes
Weekly program			No
Annual program			No
Mains synchronous			Yes
Quartz controlled			Yes
Contact type			Normally open contact
Shortest switching time channel 1		min	15
Shortest switching time channel 2		min	0
Program shift divide 1		min	15
Program shift divide 2		min	0
Automatic switching summer-/winter time			No
Manual operation			Yes
Switching preselection			Yes
Nominal switching current at 250 V AC		A	16
Potential free switch contact			Yes
Degree of protection (IP)			IP20
Width in number of modular spacings			1
Width		mm	17.5
Height		mm	90
Depth		mm	60

avrora-arm.ru
+7 (495) 956-62-18