



## Ограничитель перенапряжения, класс С, 2 полюса

Тип **SPCT2-335/2**  
 № для зак. **167599**  
 Каталог № **SPCT2-335/2**

Abbildung ähnlich

### Технические характеристики согласно ETIM 6.0

|  |                 |                               |
|--|-----------------|-------------------------------|
| Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)  |                 |                               |
| Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss8.1-27-13-08-05 [ACN278008]) |                 |                               |
| System configuration   |                 | -                             |
| Type of poles  |                 | 2                             |
| Nominal discharge surge current (8/20)   | kA              | 20                            |
| Nominal voltage AC   | V               | 335                           |
| Nominal voltage DC   | V               | 0                             |
| Max. continuous voltage AC   | V               | 335                           |
| Max. continuous voltage DC   | V               | 0                             |
| Max. PV-voltage  | V               | 0                             |
| Voltage protection level   | kV              | 1.6                           |
| Voltage protection level L-N   | kV              | 0                             |
| Voltage protection level N-PE  | kV              | 0                             |
| Short-circuit-proof  |                 | No                            |
| Mounting method  |                 | DIN rail (top hat rail) 35 mm |
| Construction size  |                 | 2 modular spacing             |
| Max. conductor cross section solid (solid, stranded)   | mm <sup>2</sup> | 25                            |
| Max. conductor cross section flexible (fine-strand)  | mm <sup>2</sup> | 0                             |
| With remote signalling contact   |                 | No                            |
| Integrated backup fuse   |                 | No                            |
| Signalling at the device   |                 | Optic                         |
| Category type 2  |                 | Yes                           |
| Degree of protection (IP)  |                 | IP20                          |