



Ограничитель перенапряжения, класс С, 1+N полюс

Тип **SPCT2-280-3+NPE/BB**
№ для зак. **167629**
Каталог № **SPCT2-280-3NPE/BB**

Abbildung ähnlich

Технические характеристики согласно ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)			
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss8.1-27-13-08-05 [ACN278008])			
System configuration			-
Type of poles			3+N/PE
Nominal discharge surge current (8/20)	kA		20
Nominal voltage AC	V		280
Nominal voltage DC	V		0
Max. continuous voltage AC	V		280
Max. continuous voltage DC	V		0
Max. PV-voltage	V		0
Voltage protection level	kV		1.4
Voltage protection level L-N	kV		0
Voltage protection level N-PE	kV		0
Short-circuit-proof			No
Mounting method			DIN rail (top hat rail) 35 mm
Construction size			4 modular spacing
Max. conductor cross section solid (solid, stranded)	mm ²		25
Max. conductor cross section flexible (fine-strand)	mm ²		0
With remote signalling contact			No
Integrated backup fuse			No
Signalling at the device			Optic
Category type 2			Yes
Degree of protection (IP)			IP20