



## Модульный контактор 230В, 25А, 2НО+2НЗ

Тип **Z-SCH230/25-22**  
 № для зак. **248849**

Abbildung ähnlich

### Bauartnachweis nach IEC/EN 61439

| Технические характеристики для подтверждения типа конструкции |           |    |     |
|---|-----------|----|-----|
| Номинальный ток для указания потери мощности                  | $I_n$     | A  | 25  |
| Потеря мощности на полюс, в зависимости от тока               | $P_{vid}$ | W  | 0   |
| Потеря мощности оборудования, в зависимости от тока           | $P_{vid}$ | W  | 6   |
| Статическая потеря мощности, не зависит от тока               | $P_{vs}$  | W  | 0   |
| Способность отдавать потери мощности                          | $P_{ve}$  | W  | 0   |
| Мин. рабочая температура                                      |           | °C | -40 |
| Макс. рабочая температура                                     |           | °C | 60  |
|   |           |    | 0   |

### Технические характеристики согласно ETIM 6.0

| Devices for distribution board-/surface mounting (EG000062) / Installation contactor for distribution board (EC001653)   |    |  |           |
|--|----|--|-----------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation contactor for distribution board (ecl@ss8.1-27-14-23-08 [AFZ820012]) |    |  |           |
| Rated operating voltage  | V  |  | 440 - 440 |
| Rated operation current  | A  |  | 25        |
| Utility category   |    |  | 1         |
| Rated excitation voltage   | V  |  | 230 - 230 |
| Voltage type (operating voltage)   |    |  | AC        |
| Voltage type (excitation voltage)  |    |  | AC        |
| Number of normally open contacts   |    |  | 2         |
| Number of normally closed contacts   |    |  | 2         |
| Max. incandescent lamp load  | W  |  | 3000      |
| Max. load fluorescent lamp   | VA |  | 1160      |
| Max. load fluorescent lamp (Duo circuit)   | VA |  | 2552      |
| Max. load fluorescent lamp (parallel compensated)  | VA |  | 1044      |
| Slider for hand switch   |    |  | No        |
| Number of modular spacings   |    |  | 2         |
| Built-in depth   | mm |  | 60        |
| Additional equipment possible  |    |  | Yes       |
| Degree of protection (IP)  |    |  | IP40      |