



Установочное реле со светодиодн. сигнализацией, 230В, 2НО

Тип **Z-RE230/SS**
 № для зак. **265193**

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Installation relay (EC001652)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation relay for distribution board (ecI@ss8.1-27-14-23-09 [AFZ821011])

| Function | | | Mechanical |
|---|--|----|------------|
| Mounting method | | | DIN rail |
| Width in number of modular spacings | | | 1 |
| Built-in depth | | mm | 60 |
| Number of normally open contacts | | | 2 |
| Number of normally closed contacts | | | 0 |
| Number of change-over contacts | | | 0 |
| Control voltage 1 | | V | 230 - 230 |
| Type of control voltage 1 | | | AC |
| Frequency control voltage 1 | | Hz | 50 - 50 |
| Control voltage 2 | | V | 0 - 0 |
| Type of control voltage 2 | | | - |
| Frequency control voltage 2 | | Hz | 0 - 0 |
| Nominal rated current | | A | 20 |
| Supply voltage | | V | 250 - 250 |
| Voltage type of supply voltage | | | AC |
| Max. incandescent lamp load | | W | 0 |
| Max. load fluorescent lamp | | VA | 0 |
| Max. load fluorescent lamp (Duo circuit) | | VA | 0 |
| Max. load fluorescent lamp (parallel compensated) | | VA | 0 |
| Max. switching current (cos phi = 0.6) | | A | 0 |

Размеры

