


Установочное реле со светодиодн. сигнализацией, 24В DC, 2НО+2НЗ
**Тип
№ для зак.**
**Z-RE23/2S20
265232**

Abbildung ähnlich

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Installation relay (EC001652)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation relay for distribution board (ecl@ss8.1-27-14-23-09 [AFZ821011])

Function		Mechanical
Mounting method		DIN rail
Width in number of modular spacings		2
Built-in depth	mm	60
Number of normally open contacts		2
Number of normally closed contacts		2
Number of change-over contacts		0
Control voltage 1	V	24 - 24
Type of control voltage 1		DC
Frequency control voltage 1	Hz	0 - 0
Control voltage 2	V	0 - 0
Type of control voltage 2		-
Frequency control voltage 2	Hz	0 - 0
Nominal rated current	A	20
Supply voltage	V	250 - 250
Voltage type of supply voltage		AC
Max. incandescent lamp load	W	0
Max. load fluorescent lamp	VA	0
Max. load fluorescent lamp (Duo circuit)	VA	0
Max. load fluorescent lamp (parallel compensated)	VA	0
Max. switching current ($\cos \phi = 0.6$)	A	0

Размеры

