

**Импульсное реле 48 В, 2НО+2НЗ**

**Тип**  
**№ для зак.**
**Z-S48/2S20**  
**265540**

Abbildung ähnlich

**Технические характеристики согласно ETIM 6.0**

Devices for distribution board-/surface mounting (EG000062) / Latching relay (EC000188)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Latching relay for distribution board (ec@ss8.1-27-14-23-06 [AFZ818012])

Function		-
Mounting method		DIN rail
Width in number of modular spacings		2
Built-in depth	mm	60
Number of normally open contacts		2
Number of normally closed contacts		2
Number of change-over contacts		0
Control voltage 1	V	48 - 48
Type of control voltage 1		AC
Frequency control voltage 1	Hz	50 - 50
Control voltage 2	V	24 - 24
Type of control voltage 2		DC
Frequency control voltage 2	Hz	50 - 50
Rated switch current	A	32
Supply voltage	V	240 - 415
Voltage type of supply voltage		AC
Max. incandescent lamp load	W	0
Max. load fluorescent lamp	VA	0
Max. load fluorescent lamp (Duo circuit)	VA	0
Max. load fluorescent lamp (parallel compensated)	VA	0
Max. switching current ( $\cos \phi = 0.6$ )	A	0
Manual operation possible		Yes