



## Выключатель нагрузки, 63А, 1 полюс

**Тип** IS-63/1  
**№ для зак.** 276274  
**Каталог №** IS-63/1

Abbildung ähnlich

### Программа поставок

Основная функция			Главные переключатели для работы под нагрузкой
Полюсы			1-полюсный
Применение			Коммутационные устройства для применения в промышленности и мелком производстве
Расчетный рабочий ток	$I_n$	A	63
Ассортимент			IS
графические условные обозначения			

### Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Мин. рабочая температура		°C	-5
Макс. рабочая температура		°C	40

### Технические характеристики согласно ETIM 6.0

Switching function			-
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of poles			1
Nominal rated current		A	63
Nominal rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	0
Short-circuit breaking capacity (I <sub>cn</sub> )		kA	2
Voltage type			AC
Forced segregation (according to DIN VDE 0113)			No
With signal lamp			No
Colour calotte			Not applicable
Lamp type			Not applicable
Lamp socket			Not applicable
Max. lamp power		W	0
Width in number of modular spacings			1
Built-in depth		mm	69.5
Degree of protection (IP)			IP40

## Размеры

