



Выключатель нагрузки, 100А, 1 полюс

Тип IS-100/1
№ для зак. 276282
Каталог № IS-100/1

Abbildung ähnlich

Программа поставок

Основная функция			Главные переключатели для работы под нагрузкой
Полюсы			1-полюсный
Применение			Коммутационные устройства для применения в промышленности и мелком производстве
Расчетный рабочий ток	I_n	A	100
Ассортимент			IS
графические условные обозначения			

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Мин. рабочая температура		°C	-5
Макс. рабочая температура		°C	40

Технические характеристики согласно ETIM 6.0

Switching function			-
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of poles			1
Nominal rated current		A	100
Nominal rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	0
Short-circuit breaking capacity (I _{cn})		kA	2
Voltage type			AC
Forced segregation (according to DIN VDE 0113)			No
With signal lamp			No
Colour calotte			Not applicable
Lamp type			Not applicable
Lamp socket			Not applicable
Max. lamp power		W	0
Width in number of modular spacings			1
Built-in depth		mm	69.5
Degree of protection (IP)			IP40

Размеры

