



## Выключатель-разъединитель

Тип **ZP-A63/2**  
 № для зак. **284907**

Abbildung ähnlich

### Технические характеристики согласно ETIM 6.0

| Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)                                                                                                                                   |  |    |                |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|----------------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss8.1-27-14-23-01 [AFZ813011]) |  |    |                |
| Switching function                                                                                                                                                                                                                            |  |    | Off switch     |
| Number of normally open contacts                                                                                                                                                                                                              |  |    | 0              |
| Number of normally closed contacts                                                                                                                                                                                                            |  |    | 0              |
| Number of change-over contacts                                                                                                                                                                                                                |  |    | 0              |
| Number of poles                                                                                                                                                                                                                               |  |    | 2              |
| Nominal rated current                                                                                                                                                                                                                         |  | A  | 63             |
| Nominal rated voltage                                                                                                                                                                                                                         |  | V  | 400            |
| Min. rated voltage                                                                                                                                                                                                                            |  | V  | 230            |
| Rated switching capacity                                                                                                                                                                                                                      |  | kA | 0              |
| Short-circuit breaking capacity (I <sub>cw</sub> )                                                                                                                                                                                            |  | kA | 3              |
| Voltage type                                                                                                                                                                                                                                  |  |    | AC             |
| Forced segregation (according to DIN VDE 0113)                                                                                                                                                                                                |  |    | No             |
| With signal lamp                                                                                                                                                                                                                              |  |    | No             |
| Colour calotte                                                                                                                                                                                                                                |  |    | Not applicable |
| Lamp type                                                                                                                                                                                                                                     |  |    | Not applicable |
| Lamp socket                                                                                                                                                                                                                                   |  |    | Not applicable |
| Max. lamp power                                                                                                                                                                                                                               |  | W  | 0              |
| Width in number of modular spacings                                                                                                                                                                                                           |  |    | 2              |
| Built-in depth                                                                                                                                                                                                                                |  | mm | 60             |
| Degree of protection (IP)                                                                                                                                                                                                                     |  |    | IP40           |