

DIGITAL CLAMP TESTER

AC CURRENT/LEAKAGE

FOR LEAKAGE CURRENT

Model MCL-500RMS

50mA~500A 5 ranges

True RMS 40mmφ CT



FEATURES

- 20 times/sec. high speed sampling with True RMS reading.
- High speed response for max hold enables the measurement for the instantaneous tripping leakage current of the circuit breaker.

SPECIFICATIONS

Measuring method	Dual integration mode	
Display	3 3/4 digit LCD	
Accuracy	(23°C±5°C, 80% RH or less)	
Range	Resolution	Accuracy
50mA	0.01A	±1.0% rdg ±5dgt (50/60Hz)
500mA	0.1mA	
50A	0.01A	
500A	0.1A	±1.0% rdg ±2% of F.S.
ACV (0~600V) /Resistance (0~2KHz)	0.1V/1Ω	±1.0% rdg ±5dgt (50/60Hz)
A/D conversion	True rms reading	
Jaw opening capability	40mmφ	
Overload indication	"OL" mark on LCD readout	
Maximum indication	5000	
Low battery indication	"B" mark on LCD readout	
Data hold indication	"DATA" mark on LCD readout	
Max.hold indication	"MAX" mark on LCD readout	
Affection of magnetic field	3mA or less (At 100A near by conductor)	
Sampling	20 times/s	
Limitation of circuit voltage	Less than AC 600V	
Operating temperature	0 °C to 40 °C,<80% RH	
Storage temperature	-10°C to 60°C,<70% RH	
Power supply	6LR61 or AC adaptor	
Withstanding voltage	AC2000V,1minute	
Size	69(W)×207(H)×33(D)mm	
Weight	Approx.450g	
Accessories	Carrying case 1 Instruction manual 1	
Optional accessory	AC adaptor (DC9V)	