

SCHUCK PIG LAUNCHER TYPE SMO

For reliable pig launching in a pipeline system.



SCHUCK PIG LAUNCHER TYPE SMO

For reliable pig launching in a pipeline system.



APPLICATIONS

Media: oil, gas, flammable liquids
Under and above ground installation
PN16, 25, 40, 70, 100, 150
CLASS 150 to 900 to DN1600
Temperature range -10°C to 50°C
Special design -40°C to 150°C

MANUFACTURING AND TESTING

DIN 2470 Part 1
DVGW Arbeitsblatt G 463
TRFL
ASME Code and other international standards or specifications
Certificate EN 10204, 3.1 and 3.2
PEO 97/23/EC



PRODUCT FEATURES

- » Welded steel construction with manually operated quick-action bayonet closure
- » Choice of flange or welded joint
- » With pig sensor
- » Corrosion protection as required
- » In accordance with drawing specified by customer, otherwise standard as shown in sketch
- » Surfaces sand-blasted (optional)



DESIGN

- Coupling ring with lip seal, nitrile rubber quality
- Cover with catch recesses on the bayonet teeth
- Safety device
- Bayonet lock and pressure warning device for the opening process
- Apparatus for turning the cover, with catch device
- Replacement lip seal for the bayonet closure

STANDARD MATERIALS

Materials according to standard, specification or customer specification.