#### PRODUCT SHEET

# B80AS


The B80AS is built on the successful 80 platform and adds the advantages of our patented AsyMatrix® technology to deliver increased thermal performance and reduced pressure drop. The B80AS shares the same physical aspects of the current B80, enabling it to be used as a drop-in improvement in existing systems. Target applications for the B80AS are in heat pump and chiller installations, and in transmission oil cooling and heating.




## **Basic specifications**

Maximum number of plates (NoP)	140	
maximum number of plates (NOP)	140	
Max flow	17 m³/h (74.85 gpm)	
Channel volume	0.1/0.122 dm <sup>3</sup> (0.0035/0.0043 ft <sup>3</sup> )	
Material	316 stainless steel plates, copper brazing	
Weight excl. connections	2.09+(0.164*NoP) kg 4.61+(0.362*NoP) lb	

#### Standard dimensions





#     MM     N       A     526     20.71       B     119     4.69       c     470     18.5       p     63     2.48       F     4.00+2.24*(NoP)     0.16+0.09*(NoP)       G     63     0.24       F     23     0.91       E_1     27     1.06			
B   119   4.69     C   470   18.5     D   63   2.48     F   4.00+2.24*(NoP)   0.16+0.09*(NoP)     G   6   0.24     R   23   0.91	#	MM	IN
c   470   18.5     D   63   2.48     F   4.00+2.24*(NoP)   0.16+0.09*(NoP)     G   6   0.24     R   23   0.91	Α	526	20.71
D   63   2.48     F   4.00+2.24*(NoP)   0.16+0.09*(NoP)     G   6   0.24     R   23   0.91	В	119	4.69
F   4.00+2.24*(NoP)   0.16+0.09*(NoP)     G   6   0.24     R   23   0.91	С	470	18.5
G 6 0.24   R 23 0.91	D	63	2.48
<b>R</b> 23 0.91	F	4.00+2.24*(NoP)	0.16+0.09*(NoP)
	G	6	0.24
<b>E_1</b> 27 1.06	R	23	0.91
	E_1	27	1.06



#### Available connections




Threaded Connection Solder Connection

Combo Connection Threaded Ultra High Approved


Weld Connection Victaulic Connection

\*For specific dimensions, or information about other types of connections, please contact your SWEP sales representative.

# PED Pressure / Temperature



## UL Pressure / Temperature



## Product concept

The Brazed Plate Heat Exchanger (BPHE) is constructed as a plate package of corrugated channel plates with a filler material between each plate. During the vacuum brazing process, the filler material forms a brazed joint at every contact point between the plates, creating complex channels. The BPHE allows media at different temperatures to come into close proximity, separated only by channel plates that enable heat from one media to be transferred to the other with very high efficiency. The concept is similar to other plate and frame technology, but without the gaskets and frame parts.

## **3rd party Approvals**

Most SWEP products are approved by below listed certification organizations: Europe, Pressure Equipment Directive (PED) America, Underwriters Laboratories Inc (UL) Japan, Kouatsu-Gas Hoan Kyoukai (KHK) Additionally SWEP holds approvals from a vast variety of other certification organizations. For more details please contact your local SWEP representative. SWEP reserves the right to make changes without prior notice.

## Find product solution - SSP

With SWEP's unique SSP, the SWEP Software Package, you can do advanced heat transfer calculations yourself. It's also easy to choose connections and generate drawings of the complete product. If you would like advice, SWEP offers all the service and support you need. Several SWEP accessories are also available to fulfill additional needs.

## Disclaimer

The information and recommendations in regards to the products are presented in good faith, however, SWEP makes no representations or warranties as to the completeness or accuracy of the information. Information is supplied upon the condition that the purchasers will make their own determination as to the products' suitability for their purposes prior to use. Purchasers should note that the properties of the products are both application and material selection dependent and that products containing stainless steel are still object to corrosion if used in unsuitable environments. Standard data is presented, product variants with different data may exist. Contact your SWEP sales representative for more details. SWEP may change any data without notice.

