

# Infrared hand-held thermometer Model CTR1000

WIKA data sheet CT 55.21



for further approvals  
see page 2

## Applications

- Diagnostics and monitoring
- Calibration service companies and service industry
- Industry (laboratory, workshop and production)
- Quality assurance

## Special features

- Non-contact temperature measurement
- Temperature measuring range from -60 ... +1,000 °C (-76 ... 1,832 °F)
- Dual-target laser
- Input for thermocouple
- Simple operation



Infrared hand-held thermometer model CTR1000

## Description

Infrared hand-held thermometers allow a temperature measurement from a distance, without contact with the object being measured. They can therefore be used where thermocouples and resistance thermometers cannot be used.

In particular due to their simplicity and ease of operation, infrared hand-held thermometers are the safest devices for measuring hot, difficult-to-reach or mobile objects, while avoiding damage or contamination.

Infrared hand-held thermometers are valued by experienced users in a wide range of industries, from the maintenance of machinery and equipment to food monitoring - since they measure surface temperatures quickly, reliably and accurately.

Over the past years, hand-held infrared thermometers have become an essential measuring and testing device in processes where temperature is important. Wherever the temperature significantly affects process safety and product quality, an infrared hand-held thermometer should be at hand.



Typical application examples for the quick, non-contact measurement of surface temperatures with infrared hand-held thermometers are measurements on:

- Difficult-to-access parts
- Rotating parts
- Live electrical conductors
- Dangerously hot objects
- Components with a low mass
- Aggressive materials

Specifications	Model CTR1000
Temperature measuring range	-60 ... +1,000 °C (-76 ... 1,832 °F)
Accuracy <sup>1)</sup>	2 K or 2 %
Display resolution	0.1 °C, from 200 °C 1 °C 0.1 °F, from 200 °F 1 °F
Spectral sensitivity	6 ... 14 µm
Measuring distance	up to 8 m (26.25 ft)
Emissivity	0.01 ... 1.00
Optical resolution	50 : 1
Response time	< 1 s
Temperature units	°C and °F
Power supply	2 x 1.5 Volt AAA size
Ambient temperature	0 ... 50 °C (32 ... 122 °F)
Dimensions, H x D x W	203 x 197 x 47 mm (7.99 x 7.76 x 1.85 in)
Weight	386 g (0.851 lbs)

1) The accuracy and reproducibility is specified in K and in % of the reading. The largest value is always used.

## Approvals

Logo	Description	Country
	<b>EU declaration of conformity</b> ■ EMC directive ■ RoHS directive	European Union
	<b>EAC</b> EMC directive	Eurasian Economic Community
-	<b>MTSCHS</b> Permission for commissioning	Kazakhstan

## Certificates

Certificate	
<b>Calibration</b>	Standard: 3.1 calibration certificate per EN 10204 Option: DKD/DAkkS calibration certificate
<b>Recommended recalibration interval</b>	1 year (dependent on conditions of use)

Approvals and certificates, see website

## Scope of delivery

- Infrared hand-held thermometer model CTR1000
- Operating instructions
- Batteries
- Transport case
- 3.1 calibration certificate per DIN EN 10204

## Accessories

### Probe

- Thermocouple type K

## Features

- LC display illumination
- Display hold, 20 s
- Min./Max. function
- Average value function
- Differential temperature
- Visible and audible high/low alarm
- Connection socket for thermocouple probe
- Laser – class II
- Tripod thread

## Ordering information

CTR1000 / Standard accessories / Further approvals / Additional ordering information

© 12/2008 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.  
The specifications given in this document represent the state of engineering at the time of publishing.  
We reserve the right to make modifications to the specifications and materials.