

# Hoses for SF<sub>6</sub> gas

## Model GCH-08, nominal width DN 8

## Model GCH-20, nominal width DN 20

WIKA data sheet SP 61.15

### Applications

Filling and evacuation of SF<sub>6</sub> gas tanks

### Special features

- Robust materials
- Vacuum- and pressure-tight
- Tested helium leak-tight



### Examples

## Description

### Safe operation

These hoses ensure the safe handling of the environmentally damaging greenhouse gas SF<sub>6</sub>.

Each hose is fitted with self-sealing valves and couplings and is 100% leak tested. It is thus ensured that no SF<sub>6</sub> gas can escape into the atmosphere.

### Robust

The stainless steel hoses are resistant against the common decomposition products and are, through an additional stainless steel braiding, protected against external damage. A protection cap protects the connections during transport and storage.

### Adaptable

For the connection to other nominal widths or connections, the appropriate connecting parts are available.

Connecting parts:

- Model GCx-08, nominal width DN 8
- Model GCx-20, nominal width DN 20

## Specifications

### Versions

- Stainless steel hose in accordance with DIN EN ISO 10380, nominal width DN 8, flat corrugated, single-walled, with stainless steel braiding
- Stainless steel hose in accordance with DIN EN ISO 10380, nominal width DN 20, flat corrugated, single-walled, with stainless steel braiding
- Synthetic rubber hose in accordance with SAE100 R17, nominal width DN 8

### Permissible working temperature

-40 ... +80 °C

With mounted coupling/valve

### Max. static operating pressure at 20 °C

Nominal width	Stainless steel	Rubber
DN 8	65 bar <sup>1)</sup>	65 bar <sup>1)</sup>
DN 20	55 bar	-

1) Limited through valve/coupling.

### Diameter (internal/external)

Nominal width	Stainless steel	Rubber
DN 8	8.2 mm / 13.7 mm	8 mm / 14.1 mm
DN 20	20.2 mm / 28.4 mm	-

### Minimum bending radius (dynamic/static)

Nominal width	Stainless steel	Rubber
DN 8	125 mm / 33 mm	55 mm / 55 mm
DN 20	170 mm / 70 mm	-

### Weight without connections

Nominal width	Stainless steel	Rubber
DN 8	approx. 0.2 kg/m	approx. 0.2 kg/m
DN 20	approx. 0.5 kg/m	-

### Hose length

3, 6, 12, 15 m

Other hose lengths on request.

### Connections (nominal width DN 8)

- Coupling valve, DN 8, female, aluminium (model GCC-08)
- Coupling valve, DN 8, female, stainless steel (model GCC-08)
- Valve, DN 8, male, brass (model GCV-08)
- Valve, DN 8, male, stainless steel (model GCV-08)


For details see data sheet SP 61.13

### Connections (nominal width 20 mm)

- Coupling valve, DN 20, female, brass (model GCC-20)
- Coupling valve, DN 8, female, stainless steel (model GCC-20)
- Valve, DN 8, male, brass (model GCV-20)

For details see data sheet SP 61.14

## Dimensions in mm



## Ordering information

Model / Version / Hose length / Connections

© 2017 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.  
The specifications given in this document represent the state of engineering at the time of publishing.  
We reserve the right to make modifications to the specifications and materials.

WIKA data sheet SP 61.15 · 05/2017

Page 3 of 3

05/2017 EN



**avroora-arm.ru**  
**+7 (495) 956-62-18**